

**YOUYUE**

**ZELDA**  
TIRES

# PRODUCT CATALOGUE

PASSENGER AND LIGHT TRUCK TIRES

**ADDRESS**


NO.1, FUTIAN ROAD, ZHUCHENG CITY,  
WEIFANG CITY, SHANDONG PROVINCE

**EMAIL**

export@youyuerubber.com

**WEBSITE**

www.youyuerubber.com



SHANDONG YOUYUE RUBBER TECHNOLOGY CO.LTD.

[www.youyuerubber.com](http://www.youyuerubber.com)

# YOUYUE RUBBER

## COMPANY PROFILE

PROFESSIONAL PCR TIRE MANUFACTURER

Shandong YouYue Rubber Technology Co., Ltd. is located in Zhucheng City, Weifang. It has a superior geographical location and is close to Qingdao Port.

The company is a high-tech industrial group focusing on the research and development, production, sales and foreign trade of semi-steel radial tires and related supporting products. In terms of quality control, the company has passed a number of strict certifications which fully reflects the company's high attention and strict requirements for product quality.

Relying on advanced technology and a professional team, the company is committed to providing customers with high-quality semi-steel radial tire products. In the research and development link, continuous resources are invested in innovation to meet the needs of different markets and customers. In the production process, advanced production processes and equipment are adopted to ensure the stability and reliability of products. In terms of sales and foreign trade, it actively expands domestic and foreign markets and has won wide acclaim from customers with high-quality products and services.

# WHY CHOOSE US ?



## Factory Platform

Direct tire manufacturers, enabling customers worldwide to receive the most direct and effective services.



## Quality & Services

Cutting - edge equipment and technologies, we enhance product performance and stability, and provide faster delivery services, enabling customers worldwide to enjoy a better user experience.



## Research & Development

Professional technological development, driven by continuous innovation, has led to the continuous expansion of the product line and the continuous launch of new products, ensuring a competitive edge in the market.

All of these are just to make you choose with confidence and embark on wonderful journeys around the world together

## **EVERY TIRE COUNTS**



# CONTENTS

<b>Passenger Car</b>	_____
SURATE HP .....	07
<b>Performance</b>	_____
ARCHFORCE .....	11
<b>Crossover SUV</b>	_____
SURATE HT .....	17
<b>Cargo Van</b>	_____
VANCRUISER .....	21
<b>All Terrain</b>	_____
ROLLANDER A/T .....	25
<b>Off Road</b>	_____
ROLLANDER M/T .....	29
<b>All-season Tire</b>	_____
SURATE AS .....	33
<b>Winter Tire</b>	_____
SURATE ICE03 .....	37
<b>Winter VAN Tire</b>	_____
VANCRUISER ICE .....	41

or complete warranty details, please visit:  
<https://www.youyuerubber.com/tires.html>

and see the Replacement Warranty section Or you can scan  
 this QR code to go directly to the page:



# SURATE HP



Low Noise



Comfort



Summer



Energy-saving



M+S



PASSENGER CAR



- **Quiet, safe, energy-saving, and environmentally friendly**

Designed for medium and high-end sedans. It offers exceptional comfort and remarkable noise reduction. At the same time, it excels in wetland handling and demonstrates outstanding high-speed performance.

- **Reinforced Sidewall structure**

The high turn-up design of the tire enhances its sidewall strength. It makes tires more stable in handling and ensures driving safety on complex and diverse road surfaces.

- **Low level of noise**

The slightly asymmetrical tread groove and the rationalized design of grooves provide excellent quiet comfort for driving and riding.

The knurling decoration design at the bottom of the tread groove not only brings aesthetic appearance but also reduces noise.



**HP**

# SURATE HP

Speed Symbol

**T, H, V**

Tread Width

**155-235**

Inch

**13", 14", 15", 16"**



**PERFORMANCE RATINGS**



Inch	Size	/XL	LI/SI	Rim	SW(mm)	Max Load (kg)	Max Pressure Kpa	M+S	TPMS	MSR	EV
13"	155/65R13	-	73T	4 1/2J	157	365	340	Y	✓	✓	✓
	155/70R13	-	75T	4 1/2J	157	387	300	Y	✓	✓	✓
	155/80R13	-	79T	4 1/2J	157	437	340	Y	✓	✓	✓
	165/65R13	-	77T	5J	170	412	340	Y	✓	✓	✓
	165/70R13	-	79T	5J	170	437	300	Y	✓	✓	✓
	165/80R13	-	83T	4 1/2J	165	487	340	Y	✓	✓	✓
	175/60R13	-	77T	5J	177	412	340	Y	✓	✓	✓
	175/70R13	-	82T	5J	177	475	340	Y	✓	✓	✓
	185/70R13	-	86T	5 1/2J	189	530	300	Y	✓	✓	✓
14"	155/65R14	-	75T	4 1/2J	157	387	300	Y	✓	✓	✓
	155/70R14	-	77T	4 1/2J	157	412	340	Y	✓	✓	✓
	165/60R14	-	75H	5J	170	387	340	Y	✓	✓	✓
	165/65R14	-	79T	5J	170	437	300	Y	✓	✓	✓
	165/70R14	-	81T	5J	170	462	300	Y	✓	✓	✓
	175/60R14	-	79H	5J	177	437	340	Y	✓	✓	✓
	175/65R14	-	82H	5J	177	475	300	Y	✓	✓	✓
	175/65R14	XL	86TXL	5J	177	475	300	Y	✓	✓	✓
	175/70R14	-	84T	5J	177	500	300	Y	✓	✓	✓
	185/55R14	-	80H	6J	194	450	340	Y	✓	✓	✓
	185/60R14	-	82H	5 1/2J	189	475	340	Y	✓	✓	✓
	195/60R14	-	86H	6J	201	530	340	Y	✓	✓	✓
	185/65R14	-	86H	5 1/2J	189	530	300	Y	✓	✓	✓
	185/70R14	-	88H	5 1/2J	189	560	300	Y	✓	✓	✓
	195/70R14	-	91H	6J	201	615	300	Y	✓	✓	✓
	205/60R14	-	88H	6J	209	560	340	Y	✓	✓	✓
205/70R14	-	94H	6J	209	670	340	Y	✓	✓	✓	
215/70R14	-	96H	6 1/2J	221	710	340	Y	✓	✓	✓	
15"	165/55R15	-	75V	5J	170	387	340	Y	✓	✓	✓
	165/60R15	-	77H	5J	170	412	340	Y	✓	✓	✓
	165/65R15	-	81H	5J	170	462	300	Y	✓	✓	✓
	175/50R15	-	75H	5 1/2J	182	387	340	Y	✓	✓	✓
	175/55R15	-	77V	5 1/2J	182	412	340	Y	✓	✓	✓
	175/60R15	-	81H	5J	177	462	300	Y	✓	✓	✓
	175/65R15	-	84H	5J	177	500	300	Y	✓	✓	✓
	185/55R15	-	82V	6J	194	475	300	Y	✓	✓	✓
	185/60R15	-	84H	5 1/2J	189	500	300	Y	✓	✓	✓
	185/65R15	-	88H	5 1/2J	189	560	300	Y	✓	✓	✓
	195/45R15	XL	82VXL	6 1/2J	195	475	340	Y	✓	✓	✓
	195/50R15	-	82V	6J	201	475	340	Y	✓	✓	✓
	195/55R15	-	85V	6J	201	515	300	Y	✓	✓	✓
	195/60R15	-	88V	6J	201	560	300	Y	✓	✓	✓
	195/65R15	-	91V	6J	201	615	300	Y	✓	✓	✓
	195/65R15	XL	95TXL	6J	201	615	300	Y	✓	✓	✓
	205/60R15	-	91V	6J	209	615	340	Y	✓	✓	✓
	225/60R15	-	96V	6 1/2J	228	710	340	Y	✓	✓	✓
205/65R15	-	94H	6J	209	670	300	Y	✓	✓	✓	
215/65R15	-	96H	6 1/2J	209	710	340	Y	✓	✓	✓	
205/70R15	-	96H	6J	209	710	300	Y	✓	✓	✓	
215/70R15	-	98H	6 1/2J	221	750	340	Y	✓	✓	✓	
225/70R15	-	100H	6 1/2J	228	800	340	Y	✓	✓	✓	
16"	175/55R16	-	80V	5 1/2J	182	450	300	Y	✓	✓	✓
	185/55R16	-	83V	6J	194	487	340	Y	✓	✓	✓
	195/50R16	-	84V	6J	201	500	340	Y	✓	✓	✓
	195/55R16	-	87V	6J	201	545	300	Y	✓	✓	✓
	195/60R16	-	89H	6J	201	580	300	Y	✓	✓	✓
	205/55R16	-	91V	6 1/2J	214	615	300	Y	✓	✓	✓
	205/60R16	-	92V	6J	209	630	300	Y	✓	✓	✓
	205/65R16	-	95H	6J	221	690	340	Y	✓	✓	✓
	215/55R16	-	93V	7J	226	650	340	Y	✓	✓	✓
	215/60R16	-	95H	6 1/2J	221	690	300	Y	✓	✓	✓
	225/60R16	-	98V	6 1/2J	228	750	300	Y	✓	✓	✓
	235/60R16	-	100H	7J	240	800	340	Y	✓	✓	✓
215/65R16	-	98H	6 1/2J	221	750	300	Y	✓	✓	✓	



# ARCHFORCE



Passenger Car



Low Noise



Summer



Driveability



Wet Grip



M+S



PERFORMANCE

- **The Advantages of New Asymmetrical Pattern Design**

The new asymmetrical pattern design helps the shoulder groove increase drainage performance and the middle sipe pattern improve high-speed performance. The integrated design provides excellent dry and wet road grip and handling

- **Formula with SSBR and Silicon-Containing Technology**

The formula using the latest solution polymerized styrene-butadiene rubber(SSBR) and silicon-containing technology provides excellent wetland performance and extremely low rolling resistance, as well as excellent handling during high-speed driving



**UHP**

# ARCHFORCE

Speed Symbol

**W, Y**

Tread Width

**195-305**

Inch

**16", 17", 18", 19"**

**20", 21", 22"**

Max Pressure Kpa

**340**

### PERFORMANCE RATINGS



Inch	Size	/XL	LI/SI	Rim	SW(mm)	Max Load (kg)	Max Pressure Kpa	M+S	Rim Protector	TPMS	MSR	AS
16"	195/45ZR16	XL	84W	6 1/2J	195	500	340	Y	Y	√	√	√
	205/45ZR16	XL	87W	7J	206	545	340	Y	Y	√	√	√
	215/45ZR16	XL	90W	7J	213	600	340	Y	Y	√	√	√
	205/50ZR16	XL	91W	6 1/2J	214	615	340	Y	Y	√	√	√
	205/55ZR16	XL	94W	6 1/2J	214	670	340	Y	Y	√	√	√
	215/55ZR16	XL	97W	7J	226	730	340	Y	Y	√	√	√
	225/55ZR16	XL	99W	7J	233	775	340	Y	Y	√	√	√
17"	195/40ZR17	XL	81W	7J	200	462	340	Y	Y	√	√	√
	205/40ZR17	XL	84W	7 1/2J	212	500	340	Y	Y	√	√	√
	215/40ZR17	XL	87W	7 1/2J	218	545	340	Y	Y	√	√	√
	245/40ZR17	XL	95W	8 1/2J	248	690	340	Y	Y	√	√	√
	195/45ZR17	XL	85W	6 1/2J	195	515	340	Y	Y	√	√	√
	205/45ZR17	XL	88W	7J	206	560	340	Y	Y	√	√	√
	215/45ZR17	XL	91W	7J	213	615	340	Y	Y	√	√	√
	225/45ZR17	XL	94Y	7 1/2J	225	670	340	Y	Y	√	√	√
	235/45ZR17	XL	97W	8J	236	730	340	Y	Y	√	√	√
	245/45ZR17	XL	99W	8J	243	775	340	Y	Y	√	√	√
	205/50ZR17	XL	93W	6 1/2J	214	650	340	Y	Y	√	√	√
	215/50ZR17	XL	95W	7J	226	690	340	Y	Y	√	√	√
	225/50ZR17	XL	98W	7J	233	750	340	Y	Y	√	√	√
	235/50ZR17	XL	100W	7 1/2J	245	800	340	Y	Y	√	√	√
	205/55ZR17	XL	95W	6 1/2J	214	690	340	Y	Y	√	√	√
215/55ZR17	XL	98W	7J	226	750	340	Y	Y	√	√	√	
225/55ZR17	XL	101W	7J	233	825	340	Y	Y	√	√	√	
235/55ZR17	XL	103W	7 1/2J	245	875	340	Y	Y	√	√	√	
18"	215/35ZR18	XL	84W	7 1/2J	218	500	340	Y	Y	√	√	√
	225/35ZR18	XL	87Y	8J	230	545	340	Y	Y	√	√	√
	245/35ZR18	XL	92Y	8 1/2J	248	630	340	Y	Y	√	√	√
	255/35ZR18	XL	94W	9J	260	670	340	Y	Y	√	√	√
	265/35ZR18	XL	97Y	9 1/2J	271	730	340	Y	Y	√	√	√
	275/35ZR18	XL	99W	9 1/2J	278	775	340	Y	Y	√	√	√
	215/40ZR18	XL	89Y	7 1/2J	218	580	340	Y	Y	√	√	√
	225/40ZR18	XL	92Y	8J	230	630	340	Y	Y	√	√	√
	235/40ZR18	XL	95Y	8 1/2J	241	690	340	Y	Y	√	√	√
	245/40ZR18	XL	97Y	8 1/2J	248	730	340	Y	Y	√	√	√
	255/40ZR18	XL	99Y	9J	260	775	340	Y	Y	√	√	√
	265/40ZR18	XL	101W	9 1/2J	271	825	340	Y	Y	√	√	√
	275/40ZR18	XL	103W	9 1/2J	278	875	340	Y	Y	√	√	√
	215/45ZR18	XL	93Y	7J	213	650	340	Y	Y	√	√	√
	225/45ZR18	XL	95Y	7 1/2J	225	690	340	Y	Y	√	√	√
	235/45ZR18	XL	98W	8J	236	750	340	Y	Y	√	√	√
	245/45ZR18	XL	100Y	8J	243	800	340	Y	Y	√	√	√
	255/45ZR18	XL	103Y	8 1/2J	255	875	340	Y	Y	√	√	√
215/50ZR18	XL	96W	7J	226	710	340	Y	Y	√	√	√	
225/50ZR18	XL	99W	7J	233	775	340	Y	Y	√	√	√	
235/50ZR18	XL	101W	7 1/2J	245	825	340	Y	Y	√	√	√	
245/50ZR18	XL	104W	7 1/2J	253	900	340	Y	Y	√	√	√	
255/50ZR18	XL	106W	8J	265	950	340	Y	Y	√	√	√	
215/55ZR18	XL	99W	7J	226	775	340	Y	Y	√	√	√	
225/55ZR18	XL	102W	7J	233	850	340	Y	Y	√	√	√	
235/55ZR18	XL	104W	7 1/2J	245	900	340	Y	Y	√	√	√	
255/55ZR18	XL	109W	8J	265	1030	340	Y	Y	√	√	√	

Inch	Size	/XL	LI/SI	Rim	SW(mm)	Max Load (kg)	Max Pressure Kpa	M+S	Rim Protector	🚗	🔊	☀️	🚗
19"	255/30ZR19	XL	91Y	9J	260	615	340	Y	Y	✓	✓	✓	✓
	275/30ZR19	XL	96Y	9 1/2J	278	710	340	Y	Y	✓	✓	✓	✓
	225/35ZR19	XL	88Y	8J	230	560	340	Y	Y	✓	✓	✓	✓
	235/35ZR19	XL	91Y	8 1/2J	241	615	340	Y	Y	✓	✓	✓	✓
	245/35ZR19	XL	93Y	8 1/2J	248	650	340	Y	Y	✓	✓	✓	✓
	255/35ZR19	XL	96Y	9J	260	710	340	Y	Y	✓	✓	✓	✓
	275/35ZR19	XL	100Y	9 1/2J	278	800	340	Y	Y	✓	✓	✓	✓
	225/40ZR19	XL	93Y	8J	230	650	340	Y	Y	✓	✓	✓	✓
	235/40ZR19	XL	96Y	8 1/2J	241	710	340	Y	Y	✓	✓	✓	✓
	245/40ZR19	XL	98Y	8 1/2J	248	750	340	Y	Y	✓	✓	✓	✓
	255/40ZR19	XL	100Y	9J	260	800	340	Y	Y	✓	✓	✓	✓
	275/40ZR19	XL	105W	9 1/2J	278	925	340	Y	Y	✓	✓	✓	✓
	225/45ZR19	XL	96Y	7 1/2J	225	710	340	Y	Y	✓	✓	✓	✓
	235/45ZR19	XL	99Y	8J	236	775	340	Y	Y	✓	✓	✓	✓
	245/45ZR19	XL	102W	8J	243	850	340	Y	Y	✓	✓	✓	✓
	255/45ZR19	XL	104W	8 1/2J	255	900	340	Y	Y	✓	✓	✓	✓
	285/45ZR19	XL	111W	9 1/2J	285	1090	340	Y	Y	✓	✓	✓	✓
	235/50ZR19	XL	103W	7 1/2J	245	875	340	Y	Y	✓	✓	✓	✓
	255/50ZR19	XL	107W	8J	265	975	340	Y	Y	✓	✓	✓	✓
	265/50ZR19	XL	110W	8 1/2J	277	1060	340	Y	Y	✓	✓	✓	✓
205/55ZR19	XL	97W	6 1/2J	214	730	340	Y	Y	✓	✓	✓	✓	
225/55ZR19	XL	103W	7J	233	875	340	Y	Y	✓	✓	✓	✓	
235/55ZR19	XL	105W	7 1/2J	245	925	340	Y	Y	✓	✓	✓	✓	
245/55ZR19	XL	107W	7 1/2J	253	975	340	Y	Y	✓	✓	✓	✓	
255/55ZR19	XL	111W	8J	265	1090	340	Y	Y	✓	✓	✓	✓	
20"	285/30ZR20	XL	99Y	10J	290	775	340	Y	Y	✓	✓	✓	✓
	245/30ZR20	XL	90Y	8 1/2J	248	600	340	Y	Y	✓	✓	✓	✓
	275/30ZR20	XL	97Y	9 1/2J	278	730	340	Y	Y	✓	✓	✓	✓
	225/35ZR20	XL	90W	8J	230	600	340	Y	Y	✓	✓	✓	✓
	235/35ZR20	XL	92W	8 1/2J	241	630	340	Y	Y	✓	✓	✓	✓
	245/35ZR20	XL	95Y	8 1/2J	248	690	340	Y	Y	✓	✓	✓	✓
	255/35ZR20	XL	97Y	9J	260	730	340	Y	Y	✓	✓	✓	✓
	275/35ZR20	XL	102Y	9 1/2J	278	850	340	Y	Y	✓	✓	✓	✓
	315/35ZR20	XL	110Y	11J	320	1060	340	Y	Y	✓	✓	✓	✓
	245/40ZR20	XL	99Y	8 1/2J	248	775	340	Y	Y	✓	✓	✓	✓
	255/40ZR20	XL	101W	9J	260	825	340	Y	Y	✓	✓	✓	✓
	275/40ZR20	XL	106W	9 1/2J	278	950	340	Y	Y	✓	✓	✓	✓
	285/40ZR20	XL	108W	10J	290	1000	340	Y	Y	✓	✓	✓	✓
	245/45ZR20	XL	103W	8J	243	875	340	Y	Y	✓	✓	✓	✓
	255/45ZR20	XL	105W	8 1/2J	255	925	340	Y	Y	✓	✓	✓	✓
	265/45ZR20	XL	108Y	9J	266	1000	340	Y	Y	✓	✓	✓	✓
	275/45ZR20	XL	110W	9J	273	1060	340	Y	Y	✓	✓	✓	✓
	235/50ZR20	XL	104W	7 1/2J	245	900	340	Y	Y	✓	✓	✓	✓
	245/50ZR20	XL	105W	7 1/2J	253	925	340	Y	Y	✓	✓	✓	✓
	255/50ZR20	XL	109W	8J	265	1030	340	Y	Y	✓	✓	✓	✓
265/50ZR20	XL	111W	8 1/2J	277	1090	340	Y	Y	✓	✓	✓	✓	
285/50ZR20	XL	116W	9J	297	1250	340	Y	Y	✓	✓	✓	✓	
235/55ZR20	XL	105W	7 1/2J	245	925	340	Y	Y	✓	✓	✓	✓	
255/55ZR20	XL	110W	8J	265	1060	340	Y	Y	✓	✓	✓	✓	
275/55ZR20	XL	117W	8 1/2J	284	1285	340	Y	Y	✓	✓	✓	✓	

Inch	Size	/XL	LI/SI	Rim	SW(mm)	Max Load (kg)	Max Pressure Kpa	M+S	Rim Protector	🚗	🔊	☀️	🚗
21"	295/35ZR21	XL	107Y	10 1/2J	301	975	340	Y	Y	✓	✓	✓	✓
	255/40ZR21	XL	102W	9J	260	850	340	Y	Y	✓	✓	✓	✓
	295/40ZR21	XL	111Y	10 1/2J	301	1090	340	Y	Y	✓	✓	✓	✓
	265/45ZR21	XL	108W	9J	266	1000	340	Y	Y	✓	✓	✓	✓
	275/45ZR21	XL	110W	9J	273	1060	340	Y	Y	✓	✓	✓	✓
	275/50ZR21	XL	113W	8 1/2J	284	1150	340	Y	Y	✓	✓	✓	✓
	22"	245/30ZR22	XL	92W	8 1/2J	248	630	340	Y	Y	✓	✓	✓
255/30ZR22		XL	95W	9J	260	690	340	Y	Y	✓	✓	✓	✓
315/30ZR22		XL	107Y	11J	320	975	340	Y	Y	✓	✓	✓	✓
265/35ZR22		XL	102Y	9 1/2J	271	850	340	Y	Y	✓	✓	✓	✓
275/35ZR22		XL	104Y	9 1/2J	278	900	340	Y	Y	✓	✓	✓	✓
285/35ZR22		XL	106Y	10J	290	950	340	Y	Y	✓	✓	✓	✓
265/40ZR22		XL	106Y	9 1/2J	271	950	340	Y	Y	✓	✓	✓	✓
275/40ZR22		XL	107W	9 1/2J	278	975	340	Y	Y	✓	✓	✓	✓
285/40ZR22		XL	110W	10J	290	1060	340	Y	Y	✓	✓	✓	✓
305/40ZR22		XL	114Y	11J	313	1180	340	Y	Y	✓	✓	✓	✓
285/45ZR22		XL	114W	9 1/2J	285	1180	340	Y	Y	✓	✓	✓	✓
305/45ZR22	XL	118W	10J	303	1320	340	Y	Y	✓	✓	✓	✓	

## UHP

# ARCHFORCE

- Excellent high-speed performance and maneuverability
- Sharp handling, Equipped with dry and wet balance technology



Passenger Car



Low Noise



Summer



Driveability

# SURATE HT



Low Noise



Comfort



Summer



Driveability



M+S



CROSSOVER SUV

- ### Advantages of Tread Groove and Shoulder Step Designs

The stepped design of the tread groove prevents stones from getting caught when driving on country roads. The decorative 3D step design on the shoulder is beautiful and heat-dissipating

- ### Tread Groove Designs for Excellent Drainage and Hydroplaning Prevention

Four main tread grooves combined with transverse tread grooves to provide excellent drainage performance to ensure driving safety in heavy rain;

The design of curved fine grooves greatly reduces the water film between the road surface and the tire on rainy days, preventing the occurrence of hydroplaning



**HT**

## SURATE HT

Speed Symbol

**H, V**

Tread Width

**215-285**

Inch

**16", 17", 18", 20"**

### PERFORMANCE RATINGS



Inch	Size	/XL	LI/SI	Rim	SW(mm)	Max Load (kg)	Max Pressure Kpa	M+S			
16"	215/70R16	-	100H	6 1/2J	221	800	300	Y	✓	✓	✓
	225/70R16	XL	107H	6 1/2J	228	975	340	Y	✓	✓	✓
	235/70R16	-	106H	7J	240	950	300	Y	✓	✓	✓
	245/70R16	XL	111H	7J	248	1090	340	Y	✓	✓	✓
	255/70R16	-	111H	7 1/2J	260	1090	300	Y	✓	✓	✓
	265/70R16	-	112H	8J	272	1120	300	Y	✓	✓	✓
	275/70R16	-	114H	8J	279	1180	300	Y	✓	✓	✓
17"	215/60R17	XL	100H	6 1/2J	221	800	340	Y	✓	✓	✓
	225/60R17	-	99V	6 1/2J	228	875	340	Y	✓	✓	✓
	235/60R17	XL	106H	7J	240	950	340	Y	✓	✓	✓
	255/60R17	XL	110H	7 1/2J	260	1060	340	Y	✓	✓	✓
	215/65R17	-	99V	6 1/2J	221	775	300	Y	✓	✓	✓
	225/65R17	-	102H	6 1/2J	228	950	340	Y	✓	✓	✓
	235/65R17	-	104V	7J	240	900	300	Y	✓	✓	✓
	245/65R17	XL	111H	7J	248	1090	340	Y	✓	✓	✓
	255/65R17	-	110H	7 1/2J	260	1060	300	Y	✓	✓	✓
	265/65R17	-	112H	8J	272	1120	300	Y	✓	✓	✓
	275/65R17	-	115H	8J	279	1215	300	Y	✓	✓	✓
	285/65R17	-	116H	8 1/2J	292	1250	300	Y	✓	✓	✓
18"	265/70R17	-	115H	8J	272	1215	300	Y	✓	✓	✓
	225/55R18	XL	102V	7J	233	750	300	Y	✓	✓	✓
	235/55R18	XL	104V	7 1/2J	245	900	340	Y	✓	✓	✓
	225/60R18	XL	104H	6 1/2J	228	900	340	Y	✓	✓	✓
	235/60R18	XL	107H	7J	240	975	340	Y	✓	✓	✓
	245/60R18	-	105H	7J	248	925	300	Y	✓	✓	✓
	255/60R18	XL	112H	7 1/2J	260	1120	340	Y	✓	✓	✓
	265/60R18	-	110H	8J	272	1060	300	Y	✓	✓	✓
	285/60R18	-	116V	8 1/2J	292	1250	300	Y	✓	✓	✓
	235/65R18	XL	110H	7J	240	1060	340	Y	✓	✓	✓
	275/65R18	-	116H	8J	279	1250	300	Y	✓	✓	✓
	255/70R18	-	113H	7 1/2J	260	1150	300	Y	✓	✓	✓
20"	265/70R18	-	116H	8J	272	1250	300	Y	✓	✓	✓
	285/50R20	XL	116H	9J	297	1250	340	Y	✓	✓	✓
	275/60R20	XL	116H	8J	279	1250	340	Y	✓	✓	✓



- Excellent driving performance and quiet comfort
- An optimized tread pattern for traction makes your driving full of fun..

# VANCRUISER



Extra Load



VAN



Summer



M+S



CARGO VAN

- **The high-strength structure can adapt to various load-bearing requirements**

- **Special exterior design**

The "lightning-shaped" decorative design on the sidewall makes the appearance of the tire beautiful and unique.

- **High-speed stability and maneuverability**

The design of three straight grooves and closed middle shoulder enhance tire strength while greatly reducing tire noise, meeting the low noise requirements of high-end light passenger vehicles;

- **excellent driving stability and handling performance**

The design of continuous tread block on shoulder provides excellent driving stability and handling performance for vehicles under high load conditions;



**VAN**

**VANCRUISER**

Speed symbol

**T**

Tread width

**155-235**

Inch

**13", 14", 15", 16"**

**17"**

### PERFORMANCE RATINGS



Inch	Size	LI/SI	PR	Rim	SW(mm)	Max Load (kg)	Max Pressure Kpa	M+S			
13"	155R13C	85/83T	6	4 1/2J	157	515/487	350	Y	√	√	√
	165R13C	96/94T	8	4 1/2J	167	710/670	450	Y	√	√	√
	175R13C	97/95T	8	5J	178	730/690	450	Y	√	√	√
14"	175/65R14C	94/92T	8	5J	177	670/630	450	Y	√	√	√
	175/70R14C	95/93T	6	5J	177	690/650	375	Y	√	√	√
	185R14C	102/100T	8	5 1/2J	188	850/800	450	Y	√	√	√
	195R14C	106/104T	8	5 1/2J	198	950/900	450	Y	√	√	√
15"	185R15C	103/102T	8	5 1/2J	188	875/850	450	Y	√	√	√
	195R15C	106/104T	8	5 1/2J	198	950/900	450	Y	√	√	√
	215/65R15C	104/102T	6	6 1/2J	221	900/850	375	Y	√	√	√
	195/70R15C	104/102T	8	6J	201	900/850	450	Y	√	√	√
	205/70R15C	106/104T	8	6J	209	950/900	450	Y	√	√	√
	215/70R15C	109/107T	8	6 1/2J	221	1030/975	450	Y	√	√	√
16"	225/70R15C	112/110T	8	6 1/2J	228	1120/1060	450	Y	√	√	√
	185/75R16C	104/102T	8	5J	184	900/850	475	Y	√	√	√
	195/60R16C	99/97T	6	6J	201	775/730	375	Y	√	√	√
	195/65R16C	104/102T	8	6J	201	900/850	475	Y	√	√	√
	195/75R16C	107/105T	8	5 1/2J	196	975/925	475	Y	√	√	√
	215/60R16C	108/106T	8	6 1/2J	221	1000/950	475	Y	√	√	√
	205/65R16C	107/105T	8	6J	209	975/925	475	Y	√	√	√
	215/65R16C	109/107T	8	6 1/2J	221	1030/975	475	Y	√	√	√
	225/65R16C	112/110T	8	6 1/2J	228	1120/1060	475	Y	√	√	√
	235/65R16C	115/113T	8	7J	240	1215/1150	475	Y	√	√	√
	215/70R16C	108/106T	6	6 1/2J	221	1000/950	375	Y	√	√	√
	205/75R16C	113/111T	10	5 1/2J	203	1150/1090	525	Y	√	√	√
17"	215/75R16C	116/114T	10	6J	216	1250/1180	525	Y	√	√	√
	225/75R16C	121/120T	10	6J	223	1450/1400	575	Y	√	√	√
	215/60R17C	109/107T	8	6 1/2J	221	1030/975	475	Y	√	√	√



- The high-strength structure can adapt to various load-bearing requirements
- Special exterior design

# ROLLANDER A/T



SUV



Off-Road  
Traction



All-terrain



Summer



Driveability



M+S



4X4  
ALL TERRAIN

- Optimize the performance of 4WD drive
- Outstanding all-terrain driving capabilities

- Unique Tiger-Tooth-Shaped Tread Blocks

The unique tiger-tooth-shaped three-dimensional tread blocks can provide excellent traction and high passability on mountain roads, muddy terrains and snowy surfaces alike. They make your vehicle stand out and be more recognizable.

- Advantages of Wider Tire Surface and Shoulder Design

The wider tire surface makes the tire stronger and more three-dimensional. The progressive thickening design on the tire shoulder ensures that the vehicle has lateral support. And the solid white and black letters highlight the quality of the tire even more.



**A/T**

**ROLLANDER A/T**

Speed symbol

**S, T, H**

Tread width

**205-285**

Inch

**15", 16", 17"**

**18", 20"**

**PERFORMANCE RATINGS**



Inch	Size	/XL	LI/SI	Rim	SW(mm)	Max Load (kg)	Max Pressure Kpa	Sidewall	M+S
15"	31X10.5R15LT	-	109S	8 1/2J	268	1030	350	White Letter	Y
	255/70R15C	-	112/110S	7 1/2J	260	1120/1060	375	White Letter	Y
	265/70R15	-	112T	8J	272	1120	300	Black Letter	Y
	215/75R15	-	100T	6J	216	800	300	Black Letter	Y
	225/75R15	-	102T	6J	223	850	300	Black Letter	Y
	235/75R15	XL	109TXL	6 1/2J	235	1030	340	Black Letter	Y
	LT235/75R15	-	104/101S	6 1/2J	235	900/825	350	White Letter	Y
16"	215R15C	-	112/110T	6J	218	1120/1060	475	White Letter	Y
	215/65R16	-	98T	6 1/2J	221	750	300	Black Letter	Y
	215/70R16	-	100T	6 1/2J	221	800	300	Black Letter	Y
	225/70R16	-	103T	6 1/2J	228	975	340	Black Letter	Y
	235/70R16	-	106T	7J	240	950	300	Black Letter	Y
	245/70R16	XL	111TXL	7J	248	1090	340	Black Letter	Y
	255/70R16	-	111T	7 1/2J	260	1090	300	Black Letter	Y
	265/70R16	-	112T	8J	272	1120	300	Black Letter	Y
	LT265/70R16	-	121/118S	8J	272	1450/1320	550	White Letter	Y
	LT225/75R16	-	115/112S	6J	223	1215/1120	550	White Letter	Y
	245/75R16	-	111T	7J	248	1090	300	Black Letter	Y
	LT245/75R16	-	120/116S	7J	248	1380/1260	550	White Letter	Y
	LT265/75R16	-	123/120S	7 1/2J	267	1550/1400	550	White Letter	Y
	LT285/75R16	-	126/123S	8J	286	1700/1550	550	White Letter	Y
LT235/85R16	-	120/116S	6 1/2J	235	1380/1260	550	White Letter	Y	
17"	205R16C	-	110/108S	6J	208	1060/1000	450	White Letter	Y
	225/60R17	-	99H	6 1/2J	228	875	340	Black Letter	Y
	235/65R17	-	104T	7J	240	900	300	Black Letter	Y
	245/65R17	-	107T	7J	248	1090	340	Black Letter	Y
	265/65R17	-	112T	8J	272	1120	300	Black Letter	Y
	LT265/65R17	-	120/117S	8J	272	1400/1285	550	White Letter	Y
	265/70R17	-	115T	8J	272	1215	300	Black Letter	Y
	LT265/70R17	-	123/120S	8J	272	1550/1400	550	White Letter	Y
18"	LT285/70R17	-	122/119S	8 1/2J	292	1500/1360	450	White Letter	Y
	265/60R18	-	110T	8J	272	1060	300	Black Letter	Y
20"	275/65R18	-	116T	8J	279	1250	300	Black Letter	Y
	275/55R20	XL	117TXL	8 1/2J	284	1285	340	Black Letter	Y



	<b>Wet Handling</b>		<b>Driveability</b>
	<b>4WD Drive</b>		<b>Tread Life</b>

# ROLLANDER M/T



SUV



Off-Road  
Traction



Summer



Driveability



M+S



4X4  
OFF ROAD



- Good at vehicle recovery in various tough terrains
- Outstanding performance, with a focus on off-road driving.

- Reinforced structure, stronger adaptability and better vehicle recovery ability

The optimized combination design of huge tread blocks and grooves provides excellent driving force, grip and anti-skid performance on unpaved roads;

Double-layer reinforced belt and special three-layer reinforced carcass design greatly improve the overall strength of the tire and meet the requirements of the worst road conditions

- Challenge harsh road conditions more confidently and enhance the driving pleasure

The design of shoulder groove special protective dam and rough shoulder reinforcement improve the anti-impact ability, thereby greatly improving the durability;

The design of single-wound hexagonal bead greatly improves the durability and stability of the tire bead.



**M/T**

**ROLLANDER M/T**

Speed Symbol

**R**

Tread Width

**215-285**

Inch

**15", 16", 17"**

**18", 20", 22"**

**PERFORMANCE RATINGS**

Off-Road Traction: **9**

Tread Life: **7**

Dry Handling: **7**

Ride Comfort: **6**

Inch	Size	LI/SI	Rim	SW(mm)	Max Load (kg)	Max Pressure Kpa	Off-Road Traction	Sidewall	M+S	POR
15"	31X10.5R15LT	109R	8 1/2J	268	109	350	Y	White Letter	Y	√
	32X11.5R15LT	113R	9J	290	113	350	Y	White Letter	Y	√
	33X12.5R15LT	108R	10J	318	108	250	Y	White Letter	Y	√
	35X12.5R15LT	113R	10J	318	113	250	Y	White Letter	Y	√
17"	33X12.5R17LT	120R	10J	318	120	450	Y	White Letter	Y	√
	35X12.5R17LT	119R	10J	318	119	450	Y	White Letter	Y	√
18"	33X12.5R18LT	118R	10J	318	118	450	Y	White Letter	Y	√
	35X12.5R18LT	118R	10J	318	118	350	Y	White Letter	Y	√
20"	33X12.5R20LT	114R	10J	318	114	450	Y	White Letter	Y	√
	35X12.5R20LT	121R	10J	318	121	450	Y	White Letter	Y	√
22"	33X12.5R22LT	109R	10J	318	109	450	Y	White Letter	Y	√

15"	LT215/75R15	100/97R	6J	216	100/97	350	Y	Black Letter	Y	√
	LT235/75R15	104/101R	6 1/2J	235	104/101	350	Y	Black Letter	Y	√
16"	LT235/70R16	110/107R	7J	240	110/107	450	Y	Black Letter	Y	√
	LT235/85R16	120/116R	6 1/2J	235	120/116	550	Y	Black Letter	Y	√
	LT245/70R16	118/115R	7J	248	118/115	550	Y	Black Letter	Y	√
	LT245/75R16	120/116R	7J	248	120/116	550	Y	Black Letter	Y	√
	LT265/75R16	119/116R	7 1/2J	267	119/116	550	Y	Black Letter	Y	√
	LT285/75R16	126/123R	8J	286	126/123	550	Y	Black Letter	Y	√
	LT315/75R16	121/118R	8 1/2J	313	121/118	450	Y	Black Letter	Y	√
17"	LT245/75R17	121/118R	7J	248	121/118	550	Y	Black Letter	Y	√
	LT265/65R17	120/117R	8J	272	120/117	550	Y	Black Letter	Y	√
	LT265/70R17	118/115R	8J	272	118/115	550	Y	Black Letter	Y	√
	LT285/70R17	126/123R	8 1/2J	292	126/123	450	Y	Black Letter	Y	√
18"	LT275/70R18	121/118R	8J	279	121/118	550	Y	Black Letter	Y	√



**Dry Handling**



**Off-Road Traction**



**4WD Drive**



**Tread Life**

 All-season TIRE

# SURATE AS



Passenger Car



All-Season



3PMSF



Comfort



M+S



  All-season TIRE

• **An all-weather tire with excellent comprehensive performance**

• **Reliable, Adaptable, Stable, Versatile, Consistent**

Excellent all-weather performance throughout the year;

Asymmetric pattern design ensures dry and wet ground and cornering handling performance.

• **Improvements in excellent formulations and structures**

All-silicon formula provides strong grip on icy wetlands.



## ALL SEASON SURATE AS

Speed symbol  
T, H, V, W

Tread width  
145-245

Inch  
13", 14", 15", 16"  
17", 18", 19"

### PERFORMANCE RATINGS



Inch	Size	/XL	LI/SI	Rim	SW(mm)	Max Load (kg)	Max Pressure Kpa	Rim Protector	3PMSF	M+S	TPMS	EV	AWD
13"	145/70R13	-	71T	4 1/2J	150	345	300	-	Y	Y	√	√	√
	145/80R13	-	75T	4J	145	387	300	-	Y	Y	√	√	√
	155/65R13	-	73T	4 1/2J	157	365	300	-	Y	Y	√	√	√
	155/70R13	-	75T	4 1/2J	157	387	300	-	Y	Y	√	√	√
	155/80R13	-	79T	4 1/2J	157	437	300	-	Y	Y	√	√	√
	185/70R13	-	86T	5 1/2J	189	530	300	-	Y	Y	√	√	√
14"	185/60R14	-	82H	5 1/2J	189	475	340	-	Y	Y	√	√	√
	155/65R14	-	75H	4 1/2J	157	387	300	-	Y	Y	√	√	√
	165/70R14	-	81H	5J	170	462	300	-	Y	Y	√	√	√
	165/65R14	-	79T	5J	170	437	300	-	Y	Y	√	√	√
	175/65R14	-	82H	5J	177	475	300	-	Y	Y	√	√	√
	185/65R14	-	86H	5 1/2J	189	530	300	-	Y	Y	√	√	√
	195/65R14	-	89H	6J	201	580	300	-	Y	Y	√	√	√
15"	175/60R15	-	81H	5J	177	462	300	-	Y	Y	√	√	√
	195/50R15	-	82V	6J	201	475	340	-	Y	Y	√	√	√
	185/55R15	-	82H	6J	194	475	300	-	Y	Y	√	√	√
	195/55R15	-	85V	6J	201	515	300	-	Y	Y	√	√	√
	185/60R15	-	84H	5 1/2J	189	500	300	-	Y	Y	√	√	√
	195/60R15	-	88V	6J	201	560	300	-	Y	Y	√	√	√
	165/65R15	-	81H	5J	170	462	300	-	Y	Y	√	√	√
	175/65R15	-	84H	5J	177	500	300	-	Y	Y	√	√	√
	185/65R15	-	88H	5 1/2J	189	560	300	-	Y	Y	√	√	√
	195/65R15	-	91V	6J	201	615	300	-	Y	Y	√	√	√
205/65R15	-	94V	6J	209	670	300	-	Y	Y	√	√	√	
16"	195/45R16	XL	84V	6 1/2J	195	500	340	-	Y	Y	√	√	√
	195/55R16	-	87V	6J	201	545	300	-	Y	Y	√	√	√
	195/60R16	-	89H	6J	201	580	300	-	Y	Y	√	√	√
	205/45R16	XL	87W	7J	206	545	340	-	Y	Y	√	√	√
	205/55R16	-	91V	6 1/2J	214	615	300	-	Y	Y	√	√	√
	205/60R16	-	92V	6J	209	630	300	-	Y	Y	√	√	√
	215/60R16	-	95V	6 1/2J	221	690	300	-	Y	Y	√	√	√
	235/60R16	-	100V	7J	240	800	340	-	Y	Y	√	√	√
	215/55R16	XL	97W	7J	226	650	340	-	Y	Y	√	√	√
	215/45ZR16	XL	90W	7J	213	600	340	Y	Y	Y	√	√	√
17"	205/45ZR17	XL	88W	7J	206	560	340	Y	Y	Y	√	√	√
	225/45ZR17	XL	94W	7 1/2J	225	670	340	Y	Y	Y	√	√	√
	235/45ZR17	XL	97W	8J	236	730	340	Y	Y	Y	√	√	√
	205/50ZR17	XL	93W	6 1/2J	214	650	340	-	Y	Y	√	√	√
	215/50ZR17	XL	95W	7J	226	690	340	-	Y	Y	√	√	√
	225/50ZR17	XL	98W	7J	233	750	340	-	Y	Y	√	√	√
	205/55R17	XL	95W	6 1/2J	214	690	340	-	Y	Y	√	√	√
	215/55R17	XL	98W	7J	226	750	340	-	Y	Y	√	√	√
	225/55R17	XL	101W	7J	233	825	340	-	Y	Y	√	√	√
	235/55R17	XL	103W	7 1/2J	245	875	340	-	Y	Y	√	√	√
	215/60R17	XL	100V	6 1/2J	221	800	340	-	Y	Y	√	√	√
	225/60R17	XL	103V	6 1/2J	228	875	340	-	Y	Y	√	√	√
	225/65R17	XL	106V	6 1/2J	228	950	340	-	Y	Y	√	√	√
235/65R17	XL	108V	7J	240	900	300	-	Y	Y	√	√	√	
18"	225/40ZR18	XL	92W	8J	230	630	340	Y	Y	Y	√	√	√
	245/40ZR18	XL	97W	8 1/2J	248	730	340	Y	Y	Y	√	√	√
	225/45ZR18	XL	95W	7 1/2J	225	690	340	Y	Y	Y	√	√	√
	215/50ZR18	XL	96W	7J	226	710	340	-	Y	Y	√	√	√
	235/50ZR18	XL	101W	7 1/2J	245	825	340	-	Y	Y	√	√	√
	225/55R18	-	98W	7J	233	750	300	-	Y	Y	√	√	√
19"	235/60R18	XL	107V	7J	240	975	340	-	Y	Y	√	√	√
	235/40ZR19	XL	96W	8 1/2J	241	710	340	Y	Y	Y	√	√	√
	235/50ZR19	XL	103W	7 1/2J	245	875	340	-	Y	Y	√	√	√
	235/55R19	XL	105W	7 1/2J	245	925	340	-	Y	Y	√	√	√
	225/35ZR19	XL	88W	8J	230	560	340	Y	Y	Y	√	√	√

WINTER TIRE 

# SURATE **ICE03**



Winter



3PMSF



Passenger Car



M+S

PASSENGER TIRE  



- **The tread's fine 3D ultra-thin groove design**

Asymmetric patterned tires maintain rigidity on the outer side and provide more contact area, improving grip on dry and wet areas as well as sharp turns on ice.

The tread's fine 3D ultra-thin groove design improves grip while ensuring excellent handling and driving performance on ice and snow.

- **Snow removal performance**

More horizontal and multiple pattern grooves intersect, which can fully absorb moisture and avoid the formation of water film. At the same time, they can effectively wrap and form snow columns to improve snow removal performance.

The low-temperature resistant mixed soft rubber formula for the tread has strong grip on snow and ice surfaces, which can ensure excellent handling performance.



**WINTER**

# SURATE *ICE03*

Speed symbol

**T, H**

Tread width

**155-315**

Inch

**13", 14", 15", 16"**

**17", 18", 19", 20"**

**21"**

### PERFORMANCE RATINGS

Wet Handing: **9**

Winter Handing: **8**

Dry Handing: **7**

Comfort: **7**

Tread Life: **7**

Inch	Size	/XL	LI/SI	Rim	SW(mm)	Max Load (kg)	Max Pressure Kpa	3PMSF	TYPE	M+S			
13"	155/70R13	-	75T	4 1/2J	157	387	300	Y	Snow	Y	✓	✓	✓
	165/70R13	-	79T	5J	170	437	300	Y	Snow	Y	✓	✓	✓
	175/70R13	-	82T	5J	177	475	340	Y	Snow	Y	✓	✓	✓
14"	165/60R14	-	75H	5J	170	387	300	Y	Snow	Y	✓	✓	✓
	185/60R14	-	82H	5 1/2J	189	475	340	Y	Snow	Y	✓	✓	✓
	155/65R14	-	75T	4 1/2J	157	387	300	Y	Snow	Y	✓	✓	✓
	165/65R14	-	79T	5J	170	437	300	Y	Snow	Y	✓	✓	✓
	175/65R14	-	82T	5J	177	475	300	Y	Snow	Y	✓	✓	✓
	185/65R14	-	86H	5 1/2J	189	530	300	Y	Snow	Y	✓	✓	✓
	165/70R14	-	81T	5J	170	462	300	Y	Snow	Y	✓	✓	✓
	175/70R14	-	84T	5J	177	500	300	Y	Snow	Y	✓	✓	✓
	185/70R14	-	88T	5 1/2J	189	560	300	Y	Snow	Y	✓	✓	✓
195/70R14	-	91T	6J	201	615	300	Y	Snow	Y	✓	✓	✓	
15"	185/55R15	-	82H	6J	194	475	300	Y	Snow	Y	✓	✓	✓
	195/55R15	-	85H	6J	201	515	300	Y	Snow	Y	✓	✓	✓
	195/60R15	-	88H	6J	201	560	300	Y	Snow	Y	✓	✓	✓
	185/60R15	-	84H	5 1/2J	189	500	300	Y	Snow	Y	✓	✓	✓
	175/65R15	-	84T	5J	177	500	300	Y	Snow	Y	✓	✓	✓
	185/65R15	-	88H	5 1/2J	189	560	300	Y	Snow	Y	✓	✓	✓
	195/50R15	-	82H	6J	201	475	340	Y	Snow	Y	✓	✓	✓
	195/65R15	XL	95TXL	6J	201	615	300	Y	Snow	Y	✓	✓	✓
	205/65R15	-	94H	6J	209	670	300	Y	Snow	Y	✓	✓	✓
205/70R15	-	96T	6J	209	710	300	Y	Snow	Y	✓	✓	✓	
16"	175/55R16	-	80H	5 1/2J	182	450	300	Y	Snow	Y	✓	✓	✓
	195/55R16	XL	91HXL	6J	201	545	300	Y	Snow	Y	✓	✓	✓
	205/55R16	-	91H	6 1/2J	214	615	300	Y	Snow	Y	✓	✓	✓
	215/55R16	XL	97HXL	7J	226	650	340	Y	Snow	Y	✓	✓	✓
	225/55R16	XL	99HXL	7J	233	775	340	Y	Snow	Y	✓	✓	✓
	195/60R16	-	89H	6J	201	580	300	Y	Snow	Y	✓	✓	✓
	205/60R16	-	92H	6J	209	630	300	Y	Snow	Y	✓	✓	✓
	215/60R16	-	95H	6 1/2J	221	690	300	Y	Snow	Y	✓	✓	✓
	225/60R16	-	98H	6 1/2J	228	750	300	Y	Snow	Y	✓	✓	✓
	205/65R16	-	95H	6J	221	690	340	Y	Snow	Y	✓	✓	✓
	215/65R16	-	98T	6 1/2J	221	750	300	Y	Snow	Y	✓	✓	✓
	215/70R16	-	100T	6 1/2J	221	800	300	Y	Snow	Y	✓	✓	✓
	235/70R16	-	106T	7J	240	950	300	Y	Snow	Y	✓	✓	✓
245/70R16	XL	111TXL	7J	248	1090	340	Y	Snow	Y	✓	✓	✓	
17"	225/45R17	XL	94HXL	7 1/2J	225	670	340	Y	Snow	Y	✓	✓	✓
	235/45R17	XL	97HXL	8J	236	730	340	Y	Snow	Y	✓	✓	✓
	205/50R17	XL	93HXL	6 1/2J	214	650	340	Y	Snow	Y	✓	✓	✓
	215/50R17	XL	95HXL	7J	226	690	340	Y	Snow	Y	✓	✓	✓
	225/50R17	XL	98HXL	7J	233	750	340	Y	Snow	Y	✓	✓	✓
	205/55R17	XL	95HXL	6 1/2J	214	690	340	Y	Snow	Y	✓	✓	✓
	215/55R17	XL	98HXL	7J	226	750	340	Y	Snow	Y	✓	✓	✓
	225/55R17	XL	101HXL	7J	233	825	340	Y	Snow	Y	✓	✓	✓
	235/55R17	XL	103HXL	7 1/2J	245	875	340	Y	Snow	Y	✓	✓	✓
	215/60R17	-	96H	6 1/2J	221	800	340	Y	Snow	Y	✓	✓	✓
	225/60R17	-	99H	6 1/2J	228	875	340	Y	Snow	Y	✓	✓	✓
	225/65R17	-	102T	6 1/2J	228	950	340	Y	Snow	Y	✓	✓	✓
	235/65R17	-	104T	7J	240	900	300	Y	Snow	Y	✓	✓	✓
265/65R17	-	112T	8J	272	1120	300	Y	Snow	Y	✓	✓	✓	
18"	225/40R18	XL	92HXL	8J	230	630	340	Y	Snow	Y	✓	✓	✓
	255/40R18	XL	99HXL	9J	260	775	340	Y	Snow	Y	✓	✓	✓
	245/40R18	XL	97HXL	8 1/2J	248	730	340	Y	Snow	Y	✓	✓	✓
	225/45R18	XL	95HXL	7 1/2J	225	690	340	Y	Snow	Y	✓	✓	✓
	235/45R18	XL	98HXL	8J	236	750	340	Y	Snow	Y	✓	✓	✓
	245/45R18	XL	100HXL	8J	243	800	340	Y	Snow	Y	✓	✓	✓
	225/50R18	XL	99HXL	7J	233	775	340	Y	Snow	Y	✓	✓	✓
	235/50R18	-	97H	7 1/2J	245	730	300	Y	Snow	Y	✓	✓	✓
	215/55R18	XL	99HXL	7J	226	775	340	Y	Snow	Y	✓	✓	✓
	225/55R18	-	98H	7J	233	750	300	Y	Snow	Y	✓	✓	✓
19"	235/55R18	XL	104HXL	7 1/2J	245	900	340	Y	Snow	Y	✓	✓	✓
	225/60R18	XL	104HXL	6 1/2J	228	900	340	Y	Snow	Y	✓	✓	✓
	235/60R18	XL	107HXL	7J	240	975	340	Y	Snow	Y	✓	✓	✓
	265/60R18	-	110T	8J	272	1060	300	Y	Snow	Y	✓	✓	✓
	245/40R19	XL	98HXL	8 1/2J	248	750	340	Y	Snow	Y	✓	✓	✓
	225/45R19	XL	96HXL	7 1/2J	225	710	340	Y	Snow	Y	✓	✓	✓
	245/45R19	XL	102HXL	8J	243	850	340	Y	Snow	Y	✓	✓	✓
	255/45R19	XL	104HXL	8 1/2J	255	900	340	Y	Snow	Y	✓	✓	✓
	235/50R19	XL	103HXL	7 1/2J	245	875	340	Y	Snow	Y	✓	✓	✓
	255/50R19	XL	107HXL	8J	265	975	340	Y	Snow	Y	✓	✓	✓
20"	225/55R19	-	99H	7J	233	775	300	Y	Snow	Y	✓	✓	✓
	235/55R19	XL	105HXL	7 1/2J	245	925	340	Y	Snow	Y	✓	✓	✓
	245/55R19	-	103H	7 1/2J	253	875	300	Y	Snow	Y	✓	✓	✓
	255/55R19	XL	111HXL	8J	265	1090	340	Y	Snow	Y	✓	✓	✓
	255/40R20	XL	101HXL	9J	260	825	340	Y	Snow	Y	✓	✓	✓
	275/40R20	XL	106HXL	9 1/2J	278	950	340	Y	Snow	Y	✓	✓	✓
	245/45R20	XL	103HXL	8J	243	875	340	Y	Snow	Y	✓	✓	✓
	255/45R20	XL	105HXL	8 1/2J	255	925	340	Y	Snow	Y	✓	✓	✓
21"	275/45R20	XL	110HXL	9J	273	1060	340	Y	Snow	Y	✓	✓	✓
	235/50R20	XL	104HXL	7 1/2J	245	900	340	Y	Snow	Y	✓	✓	✓
	245/50R20	-	102H	7 1/2J	253	850	300	Y	Snow	Y	✓	✓	✓
	255/50R20	XL	109HXL	8J	265	1030	340	Y	Snow	Y	✓	✓	✓
	235/55R20	-	102H	7 1/2J	245	850	300	Y	Snow	Y	✓	✓	✓
	265/45R21	XL	108HXL	9J	266	1000	340	Y	Snow	Y	✓	✓	✓
315/35R21	XL	111HXL	11J	320	1090	340	Y	Snow	Y	✓	✓	✓	



WINTER TIRE

# VANCRUISER ICE



Winter



3PMSF



Driveability



M+S



WINTER VAN TIRE

- Safety of driving on icy and snowy roads.

- 3D ultra-thin groove encryption design

The tread adopts two shapes of 3D ultra-thin groove encryption design with reasonable angles to improve the grip while ensuring the handling and driving performance on ice and snow.

- Excellent wear resistance and load capacity

The low-temperature resistant mixed soft rubber formula of the tread enables the tire to remain soft in cold weather. It effectively improves the grip on ice and snow roads and ensures excellent handling performance



**WINTER**

**VANCRUISER ICE**

Speed symbol

**T**

Tread width

**165-235**

Inch

**14", 15", 16"**

**PERFORMANCE RATINGS**



Inch	Size	LI/SI	PR	Rim	SW(mm)	Max Load (kg)	Max Pressure Kpa	3PMSF	TYPE	M+S				
14"	165R14C	97/95T	8	4 1/2J	165	730/690	450	Y	Snow	Y	✓	✓	✓	✓
	175R14C	99/98T	8	5J	178	775/750	450	Y	Snow	Y	✓	✓	✓	✓
	185R14C	102/100T	8	5 1/2J	188	850/800	450	Y	Snow	Y	✓	✓	✓	✓
15"	185R15C	103/102T	8	5 1/2J	188	875/850	450	Y	Snow	Y	✓	✓	✓	✓
	195/70R15C	104/102T	8	6J	201	900/850	450	Y	Snow	Y	✓	✓	✓	✓
	215/70R15C	109/107T	8	6 1/2J	221	1030/975	450	Y	Snow	Y	✓	✓	✓	✓
	225/70R15C	112/110T	8	6 1/2J	228	1120/1060	450	Y	Snow	Y	✓	✓	✓	✓
16"	215/65R15C	104/102T	6	6 1/2J	221	900/850	375	Y	Snow	Y	✓	✓	✓	✓
	205/65R16C	107/105T	8	6J	209	975/925	475	Y	Snow	Y	✓	✓	✓	✓
	215/65R16C	109/107T	8	6 1/2J	221	1030/975	475	Y	Snow	Y	✓	✓	✓	✓
	225/65R16C	112/110T	8	6 1/2J	228	1120/1060	475	Y	Snow	Y	✓	✓	✓	✓
	235/65R16C	115/113T	8	7J	240	1215/1150	475	Y	Snow	Y	✓	✓	✓	✓
	185/75R16C	104/102T	8	5J	184	900/850	475	Y	Snow	Y	✓	✓	✓	✓
	195/75R16C	107/105T	8	5 1/2J	196	975/925	475	Y	Snow	Y	✓	✓	✓	✓
	205/75R16C	110/108T	8	5 1/2J	203	1150/1090	525	Y	Snow	Y	✓	✓	✓	✓
	215/75R16C	113/111T	8	6J	216	1250/1180	525	Y	Snow	Y	✓	✓	✓	✓
	225/75R16C	116/114T	8	6J	223	1450/1400	575	Y	Snow	Y	✓	✓	✓	✓



Winter Tire



Wet Handling



Wear Resistance



Load Capacity

